

Corromix PC 820

New generation superplasticizer high range water reducer

Reference No.	TDS / ADMIX / PC820
Issue Date:	August 2017
Revision No.	1

Product Features

Corromix PC 820 is a new generation superplasticizer – high range water reducer, based on modified polycarboxylate.

Corromix PC 820 is especially recommended for concrete requiring high early age and long term strengths, whilst maintaining the workability.

Corromix PC 820 enables the production of concrete with very low W/C ratios.

Corromix PC 820 enables the production of self-leveling concrete.

Benefits

- Enhances the workability retention of concrete in hot climates.
- High water reduction ability.
- The dispersion properties of **Corromix PC 820** allow the user to optimise the cement content when a specified mechanical strength is required.

Areas of application

Corromix PC 820 is recommended for all concrete mixes where water content, improved cementitious material performance, high workability retention and very high strengths characteristics are desirable.

1. All types of cement
2. Heavy prefabrication
3. High performance concrete, ultra high performance concrete
4. Pre-stressed concrete
5. Ready-mix concrete
6. Concrete of humid, plastic or fluid consistency
7. Normal or high flowable concrete
8. High strength concrete with high workability retention
9. Compatible with Micro silica, GGBS and Fly Ash.

Description

Corromix PC 820 is a chemically stable liquid.

1. Nature : liquid
2. Colour : Brownish
3. Density : 1.05 ± 0.02
4. pH : 5 ± 2
5. Cl⁻ ion content : nil

Corromix PC 820 does not contain any purposely added calcium chloride or other chloride based components. It will not promote or contribute to corrosion of reinforcing steel in concrete.

Packaging

- Bulk
- IBC: 1000 L

Standard specifications

Corromix PC 820 conforms to ASTM C 494 Type A, F and G and BS EN 934-2.

Directions for use

Dosage

Between 0.5 and 3.5 litre per 100 kg of total cementitious material. A 2.5 % dosage of the product to the weight of cement is commonly used.

Corromix PC 820 can be added to the water before mixing the concrete. However, if needed it can be added to the concrete after mixing.

Dosage rates of **Corromix PC 820** are dependent upon desired concrete performance characteristics and variables including cement quantity and chemistry, concrete temperature and curing conditions.

Because local climate conditions vary, please contact your local Corrotech sales representative for further assistance if using outside recommended dosage ranges.

Compatibility

Corromix PC 820 is compatible with all types of Portland cement, class C and F fly ash, slag, microsilica, calcium chloride, fibers and approved air entraining admixtures.

Precaution

- Protect from frost. Use **Corromix PC 820** at a temperature above 10°C.
- Should the product freeze, its properties can be recovered after thawing and agitating thoroughly.
- This product must be stored in plastic containers. Avoid the use of PVC containers.
- Shelf life: 12 months.

Safety

Corromix PC 820 is not considered dangerous to handle. Please refer to the material safety data sheet for additional information.